Journal of Physics:
Conference Series

PURPOSE-LED PUBLISHING™

PAPER • OPEN ACCESS


Modeling of heat transport phenomena using the equations of mathematical physics

To cite this article: C Nolasco Serna *et al* 2021 *J. Phys.: Conf. Ser.* **2102** 012016

View the article online for updates and enhancements.

You may also like

- Level of development of mathematical logical thinking in the students of the agricultural areas of the Universidad Francisco de Paula Santander, Ocaña, Colombia
C L Garcia Quintero and C M Durán Chinchilla
- Applications of the Poisson and diffusion equations to materials science
C Nolasco, N J Jácome and N A Hurtado-Lugo
- Analysis of the biomass produced in the furniture factories of the municipality of Ocaña
J Arévalo, E E Espinel and M I Cabellos



This content was downloaded from IP address 8.243.64.131 on 30/09/2025 at 15:46

Modeling of heat transport phenomena using the equations of mathematical physics

C Nolasco Serna[1], **N Afanador Garcia**[2], **and G Guerrero Gómez**[3]
[1] Grupo de Investigación de la Facultad de Educación, Artes y Humanidades, Universidad Francisco de Paula Santander, Seccional Ocaña, Colombia
[2] Civil Engineering Research Group, Universidad Francisco de Paula Santander, Seccional Ocaña, Colombia
[3] Grupo de Investigación de Tecnología y Desarrollo en Ingeniería, Universidad Francisco de Paula Santander, Seccional Ocaña, Colombia

E-mail: cnolascos@ufpso.edu.co

Abstract. The study of physical phenomena that include conservative principles is part of the research field of the equations of mathematical physics. To deepen in methods to solve the equations of mathematical physics is a contribution in understanding the modeling of applications in different areas. This research studies the physical phenomenon of heat transport with convection from the viewpoint of modeling with differential equations. The advantage of working with equations is to apply the techniques of mathematical analysis and numerical methods to obtain the temperature function. In the research, the solution of the heat transport model is computed according to the analytical method of separable variables in order to represent the temperature function as a trigonometric series. With the help of a simple numerical method, it is possible to derive a scheme of calculation of the temperature function. By performing a case study, the methods are compared, and their fit is verified by simulation.

1. Introduction

The scope of physical phenomena that are suitable for modeling by using mathematical physics equations is extremely wide; an example of the above is the study of dissipative waves, problems in continuum mechanics, the Fisher equation in biology, fluid dynamics, among others [1]. A prominent place in the study of the equations of mathematical physics is reserved to the diffusion equation [2]; a particular case of physical phenomena involving the diffusion model are chemical concentrations, temperature change, material properties and energy transport [3].

In this research, the phenomenon of heat transport with convection is studied with modeling from differential equations; through a detailed development supported by analytical methods [4,5] the temperature function is computed; the outlined steps can be useful in further investigations together with the teaching in science and engineering departments. In contrast to the analytical method, the transport equation is solved with the explicit numerical method [6,7] which is very easy and straightforward. In the spirit of validating the analytical and numerical calculation of the temperature function with the use of simulation, the fit of the methods is verified.

From the numerical method proposed in the research it is possible to carry out a study of the modeling of transport phenomena by using the finite elements [8], with the finality of deepening in relevant theoretical aspects relevant to the study of partial differential equations [9].

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.
Published under licence by IOP Publishing Ltd

2. Mathematical model

The differential equation describing the physical behavior of heat transport with convection is defined by the Equation (1) [10].

$$\frac{\partial H}{\partial t} = \alpha \frac{\partial^2 H}{\partial x^2} - C \frac{\partial H}{\partial x}, 0 < x < a, \tag{1}$$

where the function H represents the temperature, α the specific heat and C the convective velocity. The Equation (2) and Equation (3) correspond to the boundary conditions and Equation (4) with the initial condition.

$$H(0,t) = 0, \tag{2}$$

$$H(a,t) = 0, \tag{3}$$

$$H(x,0) = f(x). \tag{4}$$

2.1. Analytical solution

To calculate the temperature function $H(x,t)$, let us assume that it is possible to separate the variables as indicated in the following Equation (5) [11].

$$H(x,t) = v(x)w(t). \tag{5}$$

From the Equation (1) and Equation (5) it is possible to set the Equation (6), Equation (7), and Equation (8).

$$v''(x) - \frac{C}{\alpha}v' + \lambda v(x) = 0,\ w'(t) + \lambda\alpha w(t) = 0, \tag{6}$$

$$v(0) = 0, \tag{7}$$

$$v(a) = 0. \tag{8}$$

Through the change of variable as described in Equation (9).

$$z(x) = e^{\frac{-Cx}{2\lambda}} v(x), \tag{9}$$

the function $z(x)$ satisfies the boundary Equation (10), Equation (11), and Equation (12).

$$z'' + \left(\lambda - \frac{C^2}{4\alpha^2}\right) z = 0, 0 < x < a, \tag{10}$$

$$z(0) = 0, \tag{11}$$

$$z(a) = 0. \tag{12}$$

The solution to the problem posed in the Equation (10) to Equation (12) is given by the Equation (13).

$$z_n(x) = \sin\left(\frac{n\pi x}{a}\right), \tag{13}$$

therefore, the solution of the Equation (6) to Equation (8) is given by the Equation (14).

$$v_n(x) = e^{\frac{Cx}{2\alpha}} z_n(x) = e^{\frac{Cx}{2\alpha}} \sin\left(\frac{n\pi x}{a}\right). \tag{14}$$

The solution to the function $w(t)$ comes from the Equation (15).

$$w_n(t) = e^{-\lambda_n \alpha t}, \tag{15}$$

where $\lambda_n = \frac{c^2}{4\alpha^2} + \frac{n^2\pi^2}{a^2}$. When replacing Equation (14) and Equation (15) in Equation (5) it is possible to calculate the function H_n, defined by the Equation (16).

$$H_n(x,t) = e^{\frac{Cx}{2\lambda}} e^{-\lambda_n \alpha t} \sin\left(\frac{n\pi x}{a}\right), \tag{16}$$

due to the principle of superposition the temperature function is the Equation (17).

$$H(x,t) = \sum_{n=1}^{\infty} b_n e^{\frac{Cx}{2\lambda}} e^{-\lambda_n \alpha t} \sin\left(\frac{n\pi x}{a}\right), \tag{17}$$

where the Fourier coefficient [12] b_n is defined by the Equation (18)

$$b_n = \frac{2}{a}\int_0^a f(x)\, e^{\frac{Cx}{2\lambda}} \sin\left(\frac{n\pi x}{a}\right) dx. \tag{18}$$

2.2. Numerical solution

The mathematical basis of the explicit numerical method [13] for solving the mathematical modeling of the transport Equation (1) is based on the representation of the Equation (19) by an approximation.

$$\frac{H_{i,j+1} - H_{i,j}}{k} = \alpha \frac{H_{i+1,j} - 2H_{i,j} + H_{i-1,j}}{(h)^2} - C\frac{H_{i+1,j} - H_{i,j}}{k}. \tag{19}$$

When dividing the spatial interval $(0, a)$ into equal parts, the magnitude h represents the width of each subdivision, likewise the k magnitude represents the width in the spatial interval $(0, t)$. The symbol $H_{i,j}$ in Equation (19) stand for the temperature $H(ih, jk)$. By means of an algebraic procedure in Equation (19) it is possible to express $H_{i,j+1}$ by the Equation (20).

$$H_{i,j+1} = \left(\frac{\alpha k}{h^2} - \frac{Ck}{h}\right)\left(H_{i+1,j}\right) + \left(1 - \frac{2\alpha k}{h^2} + \frac{Ck}{h}\right)\left(H_{i,j}\right) + \frac{\alpha k}{h^2} H_{i-1,j}. \tag{20}$$

3. Results and discussion

In order to validate the the solution of the transport Equation (1) by using the analytical method described in the Equation (17), we propose the mathematical system described in the Equation (21), Equation (22), Equation (23) and Equation (24).

$$\frac{\partial H}{\partial t} = 2\frac{\partial^2 H}{\partial x^2} - \frac{\partial H}{\partial x}, 0 < x < 1, \tag{21}$$

$$H(0,t) = 0, \tag{22}$$

$$H(1,\pi) = 0, \tag{23}$$

$$H(x,0) = -2e^{\frac{x}{4}}\sin(3\pi x), \tag{24}$$

By calculating the functions $v_n(x)$ and $w_n(t)$ described in the Equation (14) and Equation (15), using the mathematical framework of section 2.1, it is possible to compute the equivalent of the Equation (16) described in detail in the Equation (25).

$$H(x,t) = \sum_{n=1}^{\infty} b_n e^{\frac{x}{4} - \frac{16n^2\pi^2 t + t}{8}} \sin(n\pi x). \tag{25}$$

Matching Equation (24) and Equation (25) when $t = 0$, leds the Equation (26).

$$H(x,0) = \sum_{n=1}^{\infty} b_n e^{\frac{x}{4}} \sin(n\pi x) = -2e^{\frac{x}{4}}\sin(3\pi x), \tag{26}$$

from which $b_3 = -2$, $b_n = 0$ $(n \neq 3)$. Therefore, the function H has the form of the Equation (27).

$$H(x,t) = -2e^{\frac{x}{4} - \frac{16n^2\pi^2 t + t}{8}} \sin(3\pi x). \tag{27}$$

For the case study defined in this section in the differential Equation (21), the numerical scheme Equation (20), has the structural form of the Equation (28).

$$H_{i,j+1} = \left(\frac{2k}{h^2} - \frac{k}{h}\right)\left(H_{i+1,j}\right) + \left(1 - \frac{4k}{h^2} + \frac{k}{h}\right)\left(H_{i,j}\right) + \frac{2k}{h^2} H_{i-1,j}. \tag{28}$$

By using of computational simulation [13], it is possible to compare the analytical solution Equation (27) and the numerical scheme Equation (28), to establish the fit of both methods. Figure 1 presents two curves that calculate the temperature profile after 500 iterations.

The Figure 1 shows the behavior of the temperature profile in relation to the numerical and analytical methods; from the two curves it is possible to establish that the numerical method fits with to the analytical solution. Due to the choice of constant physical [14,15] parameters α and C throughout the computational simulation of the Equation (28), it is possible to conclude the good behavior of the curves in Figure 1. Table 1 displays the calculation of the relative error of the numerical method in relation to the analytical solution in order to demonstrate the fit of Figure 1 with a small error.




Figure 1. Contour of temperature with the numerical method and analitic method.

Table 1. Relative error of the numerical method.

Space (cm)	Relative error (500^{th}iteration)
0.0	0.0000
0.1	0.0104
0.2	0.0127
0.3	0.0044
0.4	0.0081
0.5	0.0143
0.6	0.0088
0.7	0.0045
0.8	0.0146
0.9	0.0129
1.0	0.0000

4. Conclusion

The research allowed modeling the transport phenomenon in the presence of convection with equations from mathematical physics. This approach allowed the application of differential equations techniques together with numerical methods to generate the solution of the mathematical modelling; by means of simulation it was possible to compare the analytical and numerical solutions, to conclude the fit of both methods.

References

[1] Constanda C 2016 *Solution Technique for Elementary Partial Differential Equations* (New York: CRC press)
[2] Zheng L, Zhang X 2017 *Modeling and Analysis of Modern Fluid Problems* (London: Academic Press)
[3] Versteeg H K, Malalasekera W 1995 *An Introduction to Computational Fluid Dynamics* (New York: Longman Scientific & Technical)
[4] Rani J, Kirthiga P G, Molina M, Laborda E, Rajendran L 2017 Analytical solution of the convection-diffusion equation for uniformly accessible rotating disk electrodes via the homotopy perturbation method *Journal of Electroanalytical Chemistry* **799** 175
[5] Philip J R 1994 Some exact solutions of convection-diffusion and diffusion equations *Water Resourses Research* **30(12)** 3545
[6] Aswin V S, Awasthi A, Anu C 2015 A Comparative study of numerical schemes for convection-diffusion equation *Procedia Engineering* **127** 621
[7] Salkuyeh D K 2006 On the finite difference approximation to the convection–diffusion equation *Applied Mathematics and Computation* **179(1)** 79
[8] Lesaint P 1974 Finite element methods for the transport equation *Revue Francaise D'automatique, Informatique, Recherche Opérationnelle* **8(2)** 67
[9] Braess D 2007 *Finite Elements* (Cambridge: Cambridge University Press)
[10] Hillen T, Leonard I H, Van Roessel H 2012 *Partial Differential Equations Conduction Heat Transfer* (New Jersey: John Wiley & Sons)
[11] Carslaw H S, Jaeger J C 1959 *Conduction of Heat in Solids* (New York: Oxford University Press)
[12] Tolstov G P 1962 *Fourier Series* (New York: Dover Publications)
[13] Le Veque R 2007 *Finite Difference Methods for Ordinary and Partial Differential Equations* (Philadelphia: Siam)
[14] Nolasco C, Guerrero Gómez G, Gómez J A 2019 Mathematical model of firing process of Ladrillera Ocaña, Colombia *Journal of. Physics: Conference Series* **1408(1)** 012017:1
[15] Nolasco C, Jacome N J, Hurtado N A 2019 Solution by numerical methods of the heat equation in engineering applications. Mathematical a case of study: Cooling without the use of electricity *Jornal of Physics: Conference Series* **1388(1)** 012017:1